


5PXFTM VSF

Our high efficiency pumps for semicommercial applications.





TECHNICAL FEATURES

- 3hp permanent magnets motor, made in Italy, improved efficiency
- 8 programmable speed/time simplified menus
- Rotatable LCD display / optional wall-mounting kit (PN. R356905)

EATURES	
Entroniceo	

1/

Х

Н

D

Н

W

VSF DISPLAY

4 turn opening lid	\rightarrow	Easy opening and locking
XXL pre filter basket	\rightarrow	Longer periods between cleanings
landle on the top	\rightarrow	Easier to carry
Diamond seal	\rightarrow	Increased durability and tighter seal
łydraulic isolator separating priming vater from pumping water	\rightarrow	Faster priming, less turbulence and increased efficiency

- Real time clock with 24hrs retention
- TradeGrade exclusivity, only available on Whisper and XF lines.
- RS485 Modbus communication / Optional control cable (PN. R350122)
- Inlet/Outlet ightarrow 90 mm threaded
- Ø Unions ightarrow 75 mm or 90mm
- Unions included \rightarrow Yes
- Salt resistancy \rightarrow 0.40%


350

PP

BENEFITS

TRADE Grade

Part Number	Flow	Power	output	Volt	Phase	Length	Weight
	m³/h @ 8 m	(kW)	(HP)	(V)		(mm)	(Kg)
5PXF-VSF	42	2.2	3	220-240	1~	740	28



Packaging	Length (mm)	Width (mm)	Height (mm)	Pce/Palet
Box	74	37	37	-
Palet	120	80	150	9

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners. © 2020 Pentair. All rights reserved.

www.pentairpooleurope.com | marketing.poolemea@pentair.com